

Boiling Water Dispensers

Countertop | Wall Mounted | **Premium Combination** | High Capacity

Zip

The Zip boiling water dispenser eliminates wasting time and money waiting for a kettle to boil by providing a constant supply of boiling water on demand. Up to 240 cups of boiling water can be drawn off in an hour.

The Zip also dispenses up to 175 cups of perfectly chilled and purified drinking water.

It delivers drinking water at the optimum temperature for hot and cold drinks, all from one of the most stylish dispensers available.

Key Features

- Instant boiling water at 98°C
- Provides purified chilled drinking water
- Chrome plated tap
- Advanced **3M** carbon filtration
- Safety lock - if needed - requires finger/thumb operation
- Optional font allows installation away from the sink
- Boiling and chiller system housed in base unit
- Power-Pulse™ energy-saving technology
- Available in two capacities



hot PLUS

with **3M** filtration



Boiling Water Dispensers

Zip

Dimensions

	Height mm	Width mm	Depth mm
Undercounter Unit Classic G4 240/175	395	500	465
Undercounter Unit Classic G4 160/175	337	440	430

Dimensions

	Over font
Tap	132mm
With Tap Extension	232mm

Capacity

	Boiling cups per hour	Chilled cups per hour
Undercounter Unit Classic G4 240/175	240	175
Undercounter Unit Classic G4 160/175	160	175

Installation Requirements

The unit must be connected to a potable water supply, with a minimum water pressure of 2.5 bar.

The under-sink unit should be located, if possible, directly beneath the tap and not more than 1 metre away. It must be installed with clearances of 50mm to the left and right and 65mm at rear. It is essential that the cupboard containing the under counter unit is adequately ventilated. Requires a 13amp double socket within the cupboard.

Requires permanent drainage for waste water when used with a Font

